

Readers for pets and horses

Our readers are easy to use units, capable of reading all ISO compatible microchips. Both readers are user-friendly, ergonomic and designed to not annoy the animals. They require little space and have excellent performances.



© iStockphoto

Global-Scan™ GS 110



SureSense™



Reads all FDX-B 15 digit microchips and displays the temperature of compatible temperature sensing microchips.

Technical specifications

Size: 155 x 80 x 35 mm / 155 grams

Technology: FDX-B, FDX-A, HDX

Reading distances: FDX-B: up to 10 cm / FDX-A: up to 5 cm / HDX: up to 20 cm

Standards: ISO 11784 and 11785

Memory: Up to 800 ID numbers

Frequency: 134,2 kHz

Power: Standard 9 Volts PP3 alkaline battery or PP3 rechargeable NiMH battery

Serial link: RS232 9600/N/8/1 (Tx only)

Operating temperature: - 10 °C to + 55 °C

Options: Bluetooth (10 m)

Technical specifications

Readable temperature range (of compatible temperature sensing microchips): + 33 °C to + 43 °C

Size: 166 x 63 x 29 mm / 150 grams

Technology: FDX-B

Reading distance: Up to 9,5 cm

Standards: ISO 11784 and 11785

Frequency: 134,2 kHz

Power: 2 x AA batteries (not included)

Charging battery: Mini USB

Operating temperature: - 5 °C to + 55 °C

Communication: USB, Bluetooth

